



J5M-220 Super Plus

(6x2) Prime Mover

- سارے پاکستان کا پسندیدہ پرائم موبائل (6x2) میں
- بڑا اور طاقتور ٹرانسمیشن 7+1 (بشمول "C" گئیر)
 - منطوب اور زیادہ وزن اٹھانے کی صلاحیت والے پچھلے ایکسل
 - جدید ED پینٹ کے ساتھ
 - مزید بہترین ڈیزل کی بچت



Euro-II

2 Years or
WARRANTY
120,000km
whichever
comes first

J5M - 220 Super Plus (6x2) Prime Mover

SPECIFICATIONS

MASS		TRANSMISSION		DIMENSIONS	
Permissible G.C.W (Kg)	45,000	Model	FAW CA7TB100M	Length (mm)	7325
Axle Load Distribution (kg)	ایکسل لوڈ کی تقسیم	Type	7 forward 1 reverse (inclusive of 'C' gear)	Width (mm)	2490
Front	6,500	Gear Ratio	i1=10.120/ i2=7.270/ i3=4.310/ i4=2.718/ i5=1.826/ i6=1.342/ i7=1.000	Height (mm)	2830
Rear	22,000	Reverse Shift Ratio	Ir = 9.397	Wheel Base (mm)	3800 +1350
Chassis Weight (kg)	چیمبر کا کل وزن	CLUTCH	Eaton dry type, single plate, diaphragm spring clutch, hydraulic controlled and air aided power Operating	Min. Ground Clearance	256
Total	7,600			Front overhang (mm)	1,375
Front	3,610	Type	ایکسل	Rear overhang (mm)	800
Rear	3,990	Driven Plate Dia.	φ 395 (15.5)	SUSPENSION	
PERFORMANCE		AXLES		Front	Semi-elliptic multi-leaf springs
Max. Speed (km/h)	90	Front	Reverse Elliot "I" section beam	Rear	Semi-elliptic, multi-Leaf Main Springs with auxiliary springs
Max. Gradeability (%)	32	Rear	FAW single reduction	WHEEL	
Fuel Tank Capacity (L)	400	Ratio	5.28 (7/37)	Rim	8.00-20
ENGINE		BRAKES		Wheel Type	Stud-piloted 10-hole steel disc
Model	FAWDE CA6DF2D-22	Driving Brake	Full air dual circuit brake	Tyre Size	11.00-20R
Type	Diesel, 4-stroke in-line, 6 cylinders, water cooled, turbo charged with inter cooler	Parking Brake	Spring energy storage type	No. of Tyres	11
Max. Output (hp/rpm)	220 @ 2300	Auxiliary Brake	Exhaust brake	Turning Radius (m)	8.5
Max. Torque (Nm/rpm)	770 @ 1400	STEERING		FRAME	
Displacement (cc)	6557 (6.5 litre)	Model/Type		Type	
Bore	110x115	Recirculating ball-type steering, integrated power steering		Side Rails, punching & riveted construction	
Emission Standard	Euro II	CAB		Main Rail section	
		Type		280x90x8	
		Cab over engine, front tilting 44 Angle		ELECTRICAL & LIGHTS	
		Suspension		Type	
		2-point hydraulic suspension		Earth return system, negative earthed	
		Seats Type		Battery (V/Ah)	
		Mechanical suspension Seat with 3-Point Seat Belt		2 x 12V / 150	
		Seating Capacity		Generator	
		2		1200 W	

Regional Sales Offices

Karachi
D-55/ A, S.I.T.E, Main Estate
Avenue Road, Karachi.
Tel: 021-32573251-3,
Fax: 021-32573252

Peshawar
Landi Akhun Ahmed,
Near Sarhad University,
Ring Road, Peshawar,
Tel: 091-5230003-4

Lahore (Central)
Office # 104 & 105 First Floor,
EDEN Heights, 6 Main Gulberg
Jail Road, Lahore, Tel: 042-35786805

Islamabad (North)
2nd Floor, Office # 02 Rafay Mall
Near Chowk, Peshawar Road,
Rawalpindi, Tel: 051-5166937, 5166930,
Fax: 051-5167220

FAW Highway Motors
Main National Highway,
Zulfiqarabad, Karachi,
Tel: (92-21) 34100335-8,
Fax: (92-21) 34100922

FAW S.I.T.E Motors
D-55/ A, S.I.T.E, Main Estate
Avenue Road, Karachi,
Tel: 021-32573251-3,
Fax: 021-32573262

FAW Sadiqabad Motors
KLP Road, Near Bashir Sidique,
Market, Machi Goth Sadiqabad,
Tel: 0307-2240221

FAW Abdali Motors
Bypass Muzaffar,
Garh Road, Multan,
Tel: 0307-2240221

FAW Faisalabad Motors
2 km, Sidhar Bypass
Chowk Jhang Road,
Faisalabad, Cell: 0300-0250400

FAW Central Motors
27 km, Multan Road, Opp Maraka,
Telephone, Exchange, Maraka, Lahore
Tel: 042-37541113, Cell: 0336-4750442

FAW Federal Motors
Near Zila Tax, Main GT Road,
Tarnol, Islamabad,
Cell: 0320-5519947

FAW Peshawar Motors
Landi Akhun Ahmed, Near Sarhad
University, Ring Road, Peshawar,
Tel: 091-5230003-4

Head Office / Assembly Plant: Main National Highway, Zulfiqarabad, Karachi,

Tel: (92-21) 34100335-8 Fax: (92-21) 34100922, UAN No. (92-21) 111-092-111 Website: www.alhajfaw.com